Ningbo Joiwo Explosionproof Science & Technology Co., Ltd.





HANDSFREE TELEPHONE

Product Model: JWAT413

Defend Grade: IP54

Communication System: Analogue

Material: Stainless Steel

Color: Stainless Steel (Optional)



Technical Parameters

Voltage	DC5V/1A
Standby Work Current	≤300MA
Frequency Response	250∼3000 Hz
Ringer Level	≥85dB(A)
Corrosion Grade	WF2
Ambient Temperature	-20∼+60℃
Atmospheric Pressure	80∼110KPa
Relative Humidity	≤95%
Lead Hole	1-Ø10
Weight	1.5kg
Installation	Flush mounted



Application

The Hands-free Telephone usually used in elevators, pharmaceutical factories, building intercoms and other environments with special requirements








Features


- 1. The telephone can form an independent communication system with the program-controlled exchange.
- Can be directly connected to the telecommunications network.
- After the call system is formed, each phone is an independent workstation, and the failure of one of the phones does not affect the work of the entire system.
- 4. After the call system is formed, the product has an automatic gain function, and the size of the voice does not change with the distance or the number of phones.
- 5. DECG chip, with more outstanding sound, stronger anti-interference ability, digital automatic gain, no howling or intermittent call in the hands-free state..
- 6. Robust housing, constructed of 304 stainless steel material.
- stainless steel material is acid and alkali resistant, chemical resistance is strong, and various cleaning agents can be used to clean the surface
- 8. Hands-free emergency phone.
- Vandal resistant stainless steel keypad
- 10. The circuit inside the telephone has strong anti-interference ability, stable and clear voice quality
- 11. Connection: RJ11 screw terminal pair cable.
- 12. Self-made telephone spare part available.
- 13. CE, FCC, RoHS, ISO9001 compliant.



Product Dimensions









Package

Carton size:200*130*65 (mm)

Packaging materials: Pearl cotton, Carton

Net weight: 1.5KG Gross weight: 1.8KG



86-574-58223619





https://www.joiwo.com



JOIUO 玖 沃

Ningbo Joiwo Explosionproof Science & Technology Co., Ltd.



Service and Support

Under normal use, non-human damage, free THREE YEAR WARRANTY.





